Parameters

Model	STRIP P1.9
Pixel Pitch (mm)	1.9
Pixel Density (dot/m²)	23040
LED Type	SMD1010
Module Size(mm)	405.6*76
Horizontal Viewing Angle (Deg)	140
Vertical Viewing Angle (Deg)	110
Brightness (cd/m²)	400
Grey Scale(bit)	13
Refresh Rate (Hz)	1920
Maximum Cabinet Power Consumption (W)	80
Average Cabinet Power Consumption (W)	32
Cabinet Size (mm*mm)	1216*82*22.5
Cabinet Weight (±0.25KG)	2
Cabinet Resolution (PX*PX)	576*40
Input Voltage (AC)	110V-220V
Waterproof Level	IP20
Working Environment	Indoor

Reference Cases







Seasoning Area

Refrigerator

Beverage Shelves





• No dark line between modules/Higher-resolution display









• Applied to various size of shelves




Fixed Buckle





Universal Size

Features



Protection panel



Manual Maintenance



Protection Cap

■ New protection panel, a good protection of light panels, no tools, manual maintenance, with protective covers in both sidesto prevent the lamp panels from damage during transportation and removals.

Asynchronous/Synchronous Control



Synchronous control playback



Asynchronous control -U disk/SD Card

- Asynchronous/synchronous control, varied interfaces, plug and play, easy for change play content
 - Application reference



COOKES COOK IT UP WITH COOKES COOKES

Refrigerator

Food area



Supermarket shelves